



PAINT REMOVER GEL

Removes old Decking-Oil and wood stains evenly and efficiently



6611 Clear



1 APPLICATION

Product description:

Ready-to-use, viscous paint remover especially developed for removing old existing oil surface finishes in outdoor areas. Afterwards the surface can be de-greased with Osmo Wood Reviver Power-Gel and then re-oiled.

Recommended use:

Osmo Paint Remover Gel removes old Decking-Oil and wood stains on timber decking and garden furniture made of wood. Ideal for removing oil-based surface finishes on partially weathered timber decking so that an overall oil-free wood surface is achieved.

Ingredients:

Osmo Paint Remover Gel contains non-ionic tensides

Technical Data:

Specific gravity: 1.05 +/- 0.05 g/cm³
 Odour: faint/mild, odourless after drying
 pH value: 11.0-11.5

Storage:

2 years and longer if stored in the closed original can.
 Do not expose to frost or temperatures above 30 °C!

Surface Preparation:

Before the application, remove any debris from the surface with a broom or hand broom. Cover all areas that should not be treated. Osmo Paint Remover Gel is ready to use. Do not thin. Stir well before and during use as some separation in product may occur after

some time. Before treatment with Osmo Paint Remover Gel, test the substrate. A trial application is absolutely necessary! Suitability, reaction time and required application amount can be determined on sample trial area. Caution should be taken when used on veneers! Veneers may loosen from substrate.

Methods of Application:

With a brush or Osmo Decking Cleaning Brush, apply product thick enough (approx. 200 ml/m²) on the dry surface to be cleaned, and allow the gel to react for 60 minutes (but not longer than needed!). Keep surface damp during reaction time (e.g. with a spray bottle). Afterwards scrub the surface with a lot of clear water along the wood grain. After drying, inspect the wood surface and repeat the process if necessary. Residues from Paint Remover Gel may have a negative influence on the drying and adhesive properties of subsequent coatings. Therefore, it is absolutely essential to thoroughly rinse the surface after treatment. If the wood surface should be re-oiled, the surface must be neutralized and de-greased with Osmo Wood Reviver Power-Gel after drying.

Cleaning of tools:

With soap and water.

Drying time:

Allow wood to dry thoroughly (approx. 24-48 hours) before applying a new surface coating. Lower temperatures and/or higher air humidity may increase drying times.

**Coverage:**

1 litre covers approx. 5 m² with one application.

Note:

Cover all areas that should not be treated, such as sensitive plants, porous substrates (e.g. light-coloured pebble dashed concrete, render etc.), aluminium, zinc or lacquered surfaces. Have mop water ready to rinse any surfaces (e.g. aluminium, zinc or lacquered areas) that have accidentally come into contact with the gel. Please wear safety gloves and goggles.

Caution:

Causes skin irritation. Causes serious eye irritation. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Avoid breathing mist/vapours/spray. Wash hands thoroughly after handling. Wear protective gloves/eye protection. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take off contaminated clothing and wash it before reuse. Reacts with acids with evolution of heat. Risk of splashing! Caution! Do not use with other products.

Disposal:

Dispose of leftover product and completely emptied packaging according to local official guidelines (waste code number 08 01 21*). Only completely emptied cans can be recycled.

Colour tone:

6611 Clear

Size:

0.5 l; 2.5 l; 5.0 l; 10 l

The above mentioned information is provided to the best of our knowledge however without any liability.

Version 09/20



Warning